

SITEC® Rivet blind rivet nuts with plastic moulding

Brass | Flat head | Cylindrical | Open | with washer

Note: SITEC® Rivet inner thread is produced according to standard tolerances (6H, according to ISO 68-1).

Technical information can be found on the last page.



Diameter (d)	Article number	Drilling diameter d		B	E nominal size	L ₂	e		Length (l) nominal size
		nominal size	max.				min.	max.	
M 4	24310040300	10.3	10.5	15	3.7	9	0.5	3	17.7
M 5	24310050300	10.3	10.5	15	3.7	9	0.5	3	17.7
M 6	24310060300	13	13.2	18	4.3	10	0.5	3	19.3

All technical data refer to the measure mm





Head diameter
Overall length
Thread size




Grip range

Defines the range of total thickness of the customers part (even if it consists of more than one layer)



Hole geometry

If round → diameter
If hexagonal → width across flats



Head projection after setting

Variable according to the application (setting load, material substrate, etc.)

Blind side projection after installation

Defines the clearance needed on the blind side (cannot be used for quality control)

Setting stroke

Difference of total length before and after installation

RIVKLE® Nut



RIVKLE® Stud



- RIVKLE®
- Mandrel*
- Customers part
- Anvil*
- Counter nut
- Setting tool

in accordance to chosen RIVKLE®

All technical data refer to the measure mm

